

Identification_Information:

Citation:

Citation_Information:

Originator: U.S. Geological Survey
Publication_Date: 20020801
Title: Miracle Complex Fire of Grand Junction District - 2002
Geospatial_Data_Presentation_Form:
Raster digital data.
Vector data are also available as ArcView Shape Files.
Publication_Information:
Publication_Place: Sioux Falls, South Dakota USA
Publisher: U.S. Geological Survey
Online_Linkage: <http://edc.usgs.gov>

Description:

Abstract:

The U.S. Geological Survey (USGS) has entered into a cooperative agreement with the National Park Service (NPS) to deliver satellite imagery and derivative products centered on major fires that impact national parks and other federal lands. This data set was compiled at the request of a federal land management agency and is part of a suite of products generated for a specific fire. See the National Burn Severity Mapping web site at: http://edc2.usgs.gov/fsp/severity/fire_main.asp

Purpose:

The purpose of this project is to develop a robust mapping methodology and consistent data products that allow federal land managers and fire ecologists to evaluate and compare burn severity within individual fires and between fires across various ecosystems. These products will help land managers to more effectively plan, implement and monitor fire recovery activities.

Supplemental_Information:

Fire Name: Miracle Complex
Agency: BLM
Land Management Unit: Grand Junction District
Date of Fire: 6/8/2002
Type of assessment: Initial
Acres within Fire Perimeter: 2550 (perimeter derived from DNBR image)
Landsat Path and Row: 36/33
Pre-Fire Landsat Date/Scene ID:
Landsat 7; June 15, 2000 / LE7036033000016750
Post-Fire Landsat Date/Scene ID:
Landsat 7; July 07, 2002 / LE7036033000218850
Output Dataset Projection: UTM
Spheroid Name: Clarke 1866
Datum Name: NAD27
UTM Zone: 12
Image subset Corner Coordinate
(center of upper left pixel, projection meters)
ULX: 675137 LRX: 698777
ULY: 4324663 LRY: 4305073
Image subset size:
#Rows: 654
#Columns: 789
Pixel size: 30 meters
Bounding Box:
North Lat: 39 03 19 N
South Lat: 38 52 26 N
East Long: 108 42 12 W
West Long: 108 58 52 W
Latitude and Longitude within Fire Perimeter:
Lat: 38 58 09 N

Long: 108 49 47 W

Fire Perimeter: Manually digitized from 7,4,3 false color composite.

Contact_Information:

+001 605-594-6151 or (USA) 800-252-4547

Contact_Organization_Primary:

Contact_Organization: U.S. Geological Survey

Contact_Position: CSR

Contact_Voice_Telephone: +001 605-594-6151

Contact_Address:

Address_Type: physical and mailing address

Address: 47914 252nd Street

City: Sioux Falls

State_or_Province: SD

Postal_Code: 57198-0001

Country: USA

Contact_TDD/TTY_Telephone: +001 605-594-6933

Contact_Voice_Telephone: +001 605-594-6151

Contact_Facsimile_Telephone: +001 605-594-6589

Contact_Electronic_Mail_Address: fsedc@usgs.gov

Hours_of_Service: 0800 - 1600 CT, M-F, -6 h GMT

Contact_Instructions: http://edc2.usgs.gov/fsp/severity/contact_us.asp

Data_Set_Credit: USGS and NASA

Native_Data_Set_Environment: Oracle, ERDAS Imagine, & ArcInfo

Data_Quality_Information:

Attribute_Accuracy:

Attribute_Accuracy_Report:

Three on-board calibrators (two solar, one internal) provide an absolute accuracy of 5 percent, excluding band 6.

Logical_Consistency_Report:

These Landsat data are collected from a nominal altitude of 705 kilometers in a near-polar, near-circular, sun-synchronous orbit at an inclination of 98.2 degrees, imaging the same 183-km swath of Earth's surface every 16 days.

The pixels representing the bands for the image are in the data set only once.

Completeness_Report: Fire perimeter was automated, (seed value 425, distance 325) with manual edits.

Positional_Accuracy:

Horizontal_Positional_Accuracy:

Horizontal_Positional_Accuracy_Report:

Energy reflected from Earth's surface passes through a whisk-broom scanning system and all-reflective optics before being collected by the solid-state detectors at the focal plane.

Lineage:

Process_Step:

Process_Description:

These data products are derived from Landsat Thematic Mapper data.

A pre-fire scene and a post-fire scene are analyzed to create a Differenced Normalized Burn Ratio (DNBR) image. The DNBR image portrays the variations of burn severity within the fire.

The Landsat images are terrain corrected and geometrically rectified to an Albers Conical Equal Area map projection using the National Landsat Archive Production System (NLAPS). The images are further processed to convert bands 1-5 and 7 to at-satellite-reflectance. The Normalized Burn Ratio (NBR) is computed for each date of imagery using the following formula:

$$(\text{Band 4} - \text{Band 7}) / (\text{Band 4} + \text{Band 7}) = \text{NBR}$$

The differenced NBR is computed by subtracting the post-fire NBR from the pre-fire NBR:

$$\text{PreNBR} - \text{PostNBR} = \text{DNBR}$$

Higher DNBR values are correlated with more severe burns. The DNBR image is evaluated to determine the threshold value between burned and unburned areas. The perimeter of the fire is delineated using the DNBR image. The DNBR image, the pre-fire and post-fire TM images, and a fire perimeter vector file are provided in digital format in the map projection used by the National Park Service.

Source_Used_Citation_Abbreviation: TM

Process_Date: 20020601

Source_Produced_Citation_Abbreviation: DNBR

Cloud_Cover: 10

Distribution_Information:

Distributor:

Contact_Information:

Contact_Organization_Primary:

Contact_Organization: U.S. Geological Survey

Contact_Position:

Principal Scientist

Land Cover Applications

Contact_Address:

Address_Type: mailing and physical address

Address:

47914 252nd Street

EROS Data Center

City: Sioux Falls

State_or_Province: SD

Postal_Code: 57198-0001

Country: USA

Contact_Voice_Telephone: +001 605-594-6151

Contact_TDD/TTY_Telephone: +001 605 594-6933

Contact_Facsimile_Telephone: +001 605 594-6589

Contact_Electronic_Mail_Address: fsedc@usgs.gov

Hours_of_Service: 0800 - 1600 CT, M-F, -6 h GMT

Contact_Instructions: http://edc2.usgs.gov/fsp/severity/contact_us.asp

Distribution_Liability:

No warranty expressed or implied is made by the USGS regarding the use of the data, nor does the act of distribution constitute any such warranty.

Standard_Order_Process:

Digital_Form:

Digital_Transfer_Information:

Format_Name: Geo-TIFF

Format_Version_Number: 1

Digital_Transfer_Option:

Online_Option:

Computer_Contact_Information:

Network_Address:

Network_Resource_Name: http://edc2.usgs.gov/fsp/severity/download_data.asp

Digital_Form:

Digital_Transfer_Information:

Format_Name: DNBR ArcInfo GRID

Format_Version_Number: 1

Digital_Transfer_Option:

Online_Option:

Computer_Contact_Information:

Network_Address:

Network_Resource_Name: http://edc2.usgs.gov/fsp/severity/download_data.asp

Digital_Form:

Digital_Transfer_Information:

Format_Name: shape file

Format_Version_Number: 1

Digital_Transfer_Option:

Online_Option:

Computer_Contact_Information:

Network_Address:

Network_Resource_Name: http://edc2.usgs.gov/fsp/severity/download_data.asp

Fees: No charge

Ordering_Instructions: <http://edc2.usgs.gov/fsp/severity/help.asp#ordering>

Turnaround: same day

Metadata_Reference_Information:

Metadata_Date: 20020808

Metadata_Contact:

Contact_Information:

Contact_Organization_Primary:

Contact_Organization:

USGS EROS Data Center

Science & Applications Branch

Contact_Position:

Principal Scientist

Land Cover Applications

Contact_Address:

Address_Type: mailing and physical address

Address:

47914 252nd Street

EROS Data Center

City: Sioux Falls

State_or_Province: SD

Postal_Code: 57198-0001

Country: USA

Contact_Voice_Telephone: +001 605-594-6151

Contact_TDD/TTY_Telephone: +001 605-594-6933

Contact_Facsimile_Telephone: +001 605-594-6589

Contact_Electronic_Mail_Address: fsedc@usgs.gov

Hours_of_Service: 0800 - 1600 CT, M-F, -6 h GMT

Contact_Instructions: http://edc2.usgs.gov/fsp/severity/contact_us.asp

Metadata_Standard_Name: Content Standard for Digital Geospatial Metadata

Metadata_Standard_Version: FGDC-STD-001-1998

Metadata_Access_Constraints: none

Metadata_Use_Constraints: none